



## ISOLMANT FASCIA NASTRO

7.5 cm Isolmant adhesive band. Suitable to joint Isolmant sheets together (suitable for the under-screed references).



**isolmant**FasciaNastro

THICKNESS	Approx. 3 mm
IMPACT SOUND INSULATION	The non-use of Isolmant Fascia Nastro causes a decibel loss that occurs when the Isolmant sheets are not properly sealed
INSTALLATION	Install Isolmant Fascia Nastro after trimming it as you need using a cutter.
SIZE	Strips of 7.5 cm x 50 m
PACKAGING	4 strips (equal to 200 m)

### → Conditions of use

Ideal for sealing together the sheets of resilient under screed material (especially if they have no adhesive overlapping flaps), thus preventing the passage of noise and humidity. Isolmant Fascia Nastro ensures the continuity of the resilient material. It is useful in case of "little acoustic patches" that are necessary before the installation of the screed.

### → Item specifications

Adhesive sealing strip made of expanded closed-cell cross-linked polyethylene (approx. 30 kg/m<sup>3</sup>) provided in rolls of 7.5 cm height. Thickness approx. 3 mm.

**WARNING:** This technical data sheet is not a valid specification and, if it consist of multiple pages, be sure to read the full document. This instruction are the best of our current experience but are indicative information. Assuming the liability resulting from the use of this product, it is up to the user to establish whether the product is suitable for the intended use.